
INSTALLATION INSTRUCTIONS

For Decorative Brass Louver Kits

Designed For Use With Louvered-Face Decorative Gas Appliances



These louvers are designed to replace the standard black louvers that are provided with the appliance. The brass louver kits include brass louvers that simply replace the existing black louvers to provide a touch of elegance to the appliance. These kits can be retrofitted to previously installed appliances.


The decorative brass louver kits described in this document contain all the components necessary to complete the task.

The manufacturer recommends that the installation manual provided with the appliance be read completely and understood thoroughly before proceeding with the installation of the kit. All warnings and precautions in that document apply to these instructions.

INSTALLATION

Note: Prior to installing this brass component remove all of the protective plastic coating.

Remove the existing louvers from the appliance. Louvers on older models are snapped into place over pegs located at both ends. To remove, grasp the louver firmly and twist upwards releasing the bottom of the louver with a snap. Lift the top of the louver from the pegs. Louvers on later models snap into place above the door as previously discussed, however louvers at the bottom of the appliance are slid into place over the removed left and right hand louver pivots. To install brass louvers, reverse the procedure above.



Note: Underscore is used here in place of a letter character which varies by product line. Letter shown in the first position of the Model Number is designated as follows: S = Superior, F = Fireplus, H = Hearthstar

NOTE: DIAGRAMS & ILLUSTRATIONS NOT TO SCALE.