GAS INSERTS





IRONSTRIKE GAS INSERTS



The Madison Park gas fireplace insert brings convenience and efficient heating to an existing wood-burning fireplace. Listed to fit zero-clearance factory-built and masonry fireplaces, the Madison Park gas insert turns your standard wood burning fireplace into a cost-effective heat source that displays a realistic gas fire for brilliant warmth and ambiance.

OVERVIEW

- Available in large, medium and small models to fit a wide range of fireplace sizes.
- Electronic ignition system with battery backup—still ignites and heats during a power outage.
- Outstanding heating efficiency for increased comfort and lower operating costs.
- Ceramic glass for optimum heat transfer and a protective screen*.
- Seautifully crafted high-definition ceramic fiber log set.
- State-of-the-art burn technology provides the warm glowing appearance of an authentic fire.
- Choose between several distinctive styles of accessory façades to match the look of your existing décor (required).
- Interior selections consist of black reflective porcelain or a variety of ceramic fiber liners (required).
- Mood enhancing interior illumination with six distinctive settings (large & medium models).
- Factory installed blower with six speed settings to fine tune your heating needs.
- Full-function remote control included (IPI/CPI, thermostat, flame height, blower, lighting).
- 20 year limited warranty.

MADISON PARK 34



Madison Park shown with Decco façade and Buff Rustic brick.

BTU INPUT NG: 25,000 - 38,000 BTU INPUT LP: 27,000 - 35,500 HEATING CAPACITY: 500 – 2000 square feet AFUE EFFICIENCY: 67% (NG) 73% (LP ENERGUIDE (P4) EFFICIENCY: 66% (NG) 68% (LP) BLOWER: 150-CFM REMOTE CONTROL: Standard

MADISON PARK 32

BTU INPUT NG: 23,000 - 34,000 BTU INPUT LP: 28,000 - 34,000 HEATING CAPACITY: 500 – 1,750 square feet AFUE EFFICIENCY: 71% (NG) 74% (LP ENERGUIDE (P4) EFFICIENCY: 65% (NG) 70% (LP) BLOWER: 150-CFM REMOTE CONTROL: Standard

MADISON PARK 27

BTU INPUT NG: 21,000 - 30,000 BTU INPUT LP: 20,000 - 25,000 HEATING CAPACITY: 500 – 1,500 square feet AFUE EFFICIENCY: 67% (NG) 70% (LP ENERGUIDE (P4) EFFICIENCY: 68% (NG) 71% (LP) BLOWER: 150-CFM REMOTE CONTROL: Standard

OPTIONS

FAÇADES

Choose a face style that's right for your home.



Full Face Façade





Santa Fe



Contemporary

DECORATIVE ACCENT TRIMS (For use with Full Face Facade only)



Frontier



Highliner



Iron Rail

LINER



Red Rustic



Porcelain



Buff Rustic



REMOTE

The stardard Total Comfort Remote uses an intergrated thermostat to keep your room at just the right temperature.



IRONSTRIKE GAS INSERTS

MADISON PARK CD™



The Madison Park CD gas fireplace insert adds the convenience of gas with contemporary styling to an existing wood burning fireplace. Listed to fit small zero-clearance factory-built and masonry fireplaces, the Madison Park CD turns your standard wood burning fireplace into a stylish and convenient heat source that you control with the press of a button.

OVERVIEW

- Available in large, medium and small models to fit a wide range of fireplace sizes.
- Selectronic ignition system with battery backup—still ignites and heats during a power outage.
- Outstanding heating efficiency for increased comfort and lower operating costs.
- Ceramic glass for optimum heat transfer and a protective screen*.
- State-of-the-art burn technology and glass floor media provide a stunning flame presentation.
- Choose between several distinctive styles of accessory façades to match the look of your existing décor (required).
- Interior selections consist of black reflective porcelain or a variety of ceramic fiber liners (required).
- Multiple glass media kits are available to achieve a customized finished appearance (required).
- Mood enhancing interior illumination with six distinctive settings (large & medium models).
- Factory installed blower with six speed settings to fine tune your heating needs.
- Full-function remote control included (IPI/CPI, thermostat, flame height, blower, lighting).
- ♦ 20 year limited warranty.

MADISON PARK CD 34



Madison Park CD shown with Porcelain interior and Sunset glass media.

BTU INPUT NG: 25,000 - 38,000 BTU INPUT LP: 27,000 - 35,500 HEATING CAPACITY: 500 - 2000 square feet AFUE EFFICIENCY: 68% (NG) 70% (LP ENERGUIDE (P4) EFFICIENCY: 66% (NG) 70% (LP) **BLOWER: 150-CFM REMOTE CONTROL: Standard**

MADISON PARK CD 32

BTU INPUT NG: 23,000 - 34,000 BTU INPUT LP: 28,000 - 34,000 HEATING CAPACITY: 500 – 1,750 square feet AFUE EFFICIENCY: 72% (NG) 74% (LP) ENERGUIDE (P4) EFFICIENCY: 67% (NG) 72% (LP) **BLOWER: 150-CFM REMOTE CONTROL:** Standard

MADISON PARK CD 27

BTU INPUT NG: 21,000 - 30,000 BTU INPUT LP: 20,000 - 25,00 HEATING CAPACITY: 500 - 1,500 square feet AFUE EFFICIENCY: 67% (NG) 69% (LP) ENERGUIDE (P4) EFFICIENCY: 66% (NG) 68% (LP) **BLOWER: 150-CFM REMOTE CONTROL: Standard**

OPTIONS

FAÇADES

Choose a face style that's right for your home.



Full Face Façade

Contemporary







Santa Fe



Deco

Highliner

DECORATIVE ACCENT TRIMS

(For use with Full Face Façade only)




Frontier

Porcelain



Iron Rail

LINER





GLASS MEDIA



Midnight



Sunset

REMOTE



Flat Black

The stardard Total Comfort Remote uses an intergrated thermostat to keep your room at just the right temperature.

IRONSTRIKE GAS INSERTS **RAVENNA™**



The Ravenna gas fireplace insert offers the convenience of gas, the look of a real wood fire and an efficient source of supplemental heat. Listed to fit most zero-clearance factory-built and masonry fireplaces, the Ravenna turns your standard fireplace into a cost-effective heat source and warm, beautiful gathering place.

OVERVIEW

- Available in a medium size to fit most common fireplace sizes.
- Electronic ignition models include a battery backup—still ignites and heats during a power outage.
- Outstanding heating efficiency for increased comfort and lower operating costs.
- Ceramic glass for optimum heat transfer and a protective screen*.
- Seautifully crafted high-definition ceramic fiber log set.
- State-of-the-art burn technology provides the warm glowing appearance of an authentic fire.
- Interior selection consists of a natural tan brick ceramic fiber liner (required).
- Factory installed blower with six speed settings to fine tune your heating needs.
- Full-function remote control included (IPI/CPI, thermostat, flame height, blower).
- ♦ 20 year limited warranty.

RAVENNA 40



Ravenna 40 shown with Contemporary face and Tan Brick liner.

BTU INPUT NG: 28,000 - 40,000 BTU INPUT LP: 26,000 - 37,500 HEATING CAPACITY: 500 – 2000 square feet ENERGUIDE (P4) EFFICIENCY: 67% (NG) 69% (LP) BLOWER: 150-CFM REMOTE CONTROL: Standard



FACE STYLE & FINISH



Contemporary

Black

LINER



Tan Brick

SURROUND AND TRIM

Choose your surround and trim.





REMOTE

The stardard Total Comfort Remote uses an intergrated thermostat to keep your room at just the right temperature.

RAVENNA 33

BTU INPUT NG: 24,000 - 33,000 BTU INPUT LP: 24,000 - 33,000 HEATING CAPACITY: 500 – 2000 square feet ENERGUIDE (P4) EFFICIENCY: 66% (NG) 68% (LP) BLOWER: 150-CFM REMOTE CONTROL: Standard

IRONSTRIKE GAS INSERTS BELLEVUE[™]



The Bellevue gas fireplace insert is an easy and cost-effective way to transform your existing wood fireplace into a modern heating appliance. Enjoy the heritage and heat of warming by the fire without the hassle of chopping wood or the expense of a complete fireplace overhaul.

OVERVIEW

- Available in medium and small models to fit a wide range of fireplace sizes.
- Electronic ignition system with battery backup—still ignites and heats during a power outage.
- Outstanding heating efficiency for increased comfort and lower operating costs.
- Ceramic glass for optimum heat transfer and a protective screen*.
- Seautifully crafted high-definition ceramic fiber log set.
- State-of-the-art burn technology provides the warm glowing appearance of an authentic fire.
- Choose from two full front façades that provide a clean finished appearance (required).
- Optional decorative accent trims available to match the look of your existing décor.
- Black interior creates a stark contrast for the yellow dancing flames.
- Factory installed blower with six speed settings to fine tune your heating needs.
- Optional hand-held and wall mounted remote controls available for all models.
- ♦ 20 year limited warranty.

BELLEVUE 32



Bellevue 32 shown with Full Front Façade and Highliner Decorative Accent Trim.

BTU INPUT NG: 16,000 - 28,000 BTU INPUT LP: 14,000 - 25,000 HEATING CAPACITY: 500 - 1,800 square feet AFUE EFFICIENCY: 70% (NG) 67% (LP) ENERGUIDE (P4) EFFICIENCY: 57% (NG) 61% (LP) BLOWER: 150-CFM REMOTE CONTROL: Optional

BELLEVUE 27

BTU INPUT NG: 14,000 - 25,000 BTU INPUT LP: 16,200 - 22,500 HEATING CAPACITY: 450-1625 square feet AFUE EFFICIENCY: 78% (NG) 75% (LP) ENERGUIDE (P4) EFFICIENCY: 73% (NG) 73% (LP) BLOWER: 150-CFM WREMOTE CONTROL: Optional



FULL FRONT FAÇADE



Standard

DECORATIVE ACCENT TRIMS



Frontier



Highliner




Iron Rail

REMOTES





SPECIFICATIONS



		Madison Park 27	Madison Park CD 27	Madison Park 32	Madison Park CD 32	Madison Park 34	Madison Park CD 34	Ravenna 33/40	Bellevue 27	Bellevue 32
Width	Front	26-5/8"	26-5/8"	31-5/8"	31-5/8"	33-5/8"	33-5/8"	31-1/4"	26-5/8"	31-5/8"
	Back/Rear	16-3/4"	16-3/4"	21"	21"	23"	23"	17-5/8"	16-3/4"	21"
Height	Overall	17-7/8	17-7/8"	19-3/8"	19-3/8"	23-7/8"	23-7/8"	19-3/8"	17-7/8"	19-3/8"
Depth	Overall	14-7/8"	14-7/8"	15-7/8"	15-7/8"	16-1/4"	16-1/4"	15-7/8"	14-7/8"	15-7/8"
To Centerline (CL) of 3" Flue Collar		8-3/16"	8-3/16"	9-3/4"	9-3/4"	10"	10"	13-3/8"	8-3/4"	9-3/4"

MINIMUM CLEARANCES TO COMBUSTIBLES

Hearth protection to be minimum of 3/8" thick non-combustible or equivalent, with a k factor of .84.

		Madison Park 27 & Madison Park CD 27	Madison Park 32 & Madison Park	Madison Park 34 & Madison Park	Ravenna 33	Ravenna 40	Bellevue 27	Bellevue 32
	r	CD 27	CD 32	CD 34				
A	1-1/2" Top facing to bottom of appliance	32"	32"	36"	31-1/2"	35-1/2"	26-5/8"	31-5/8"
В	Side facing or side wall to center of glass	23"	25-7/8"	26-7/8"	25-1/2"	25-1/2"	16-3/4"	21"
С	6" Mantel to bottom of appliance	34"	32"	36"	39"	43"	17-7/8	19-3/8"
D	Vertical distance from base of appliance to hearth extension	0" 4"	0" 10"	0" 10"	0" 2" 4"	0" 2" 4"	14-7/8"	15-7/8"
E	Minimum horizontal distance from front of appliance	10" 0"	2" 0"	2" 0"	13" 10" 0"	14" 10" 0"	8-3/4"	9-3/4"

	Madison Park™ 27 &	Madison Park™ 32 &	Madison Park™ 34 &	Ravenna™ 33/40		Bellevue 27	Bellevue 32
	Madison Park™ CD 27	Madison Park™ CD 32	Madison Park™ CD 34				Bolloruo oz
	26" H X 37" W	26" H X 41" W	31" H X 41" W	29" H X 41" W			
Standard Surround	26" H X 41" W	26" H X 46" W	31" H X 46" W	29" H X 48" W	Required Full Front Façade		Façade
3-рс	30" H X 37" W	33" H X 41" W	34" H X 41" W	33" H X 41" W	Medium	26" H X 37" W	25" H X 41" W
	30" H X 41" W	33" H X 46" W	34" H X 46" W	33" H X 48" W	Large	30" H X 41" W	32" H X 46" W
Standard Surround 1-pc	N/A	N/A	N/A	29" H X 41" W	*Optional 4-sided Surround Backer- Able to Be Trimmed		
4 Sided - Able to be Trimmed	38" H X 46" W	38" H X 46" W	42" H X 46" W	N/A	38" H X 46" W		(46" W
Cast Surround	N/A	N/A	N/A	30" H X 45-1/2" W		30 11 X 40 W	

* The 4-Sided Surround is compatible for use with the medium size Full Front Façades (41" x 25"-Bellevue 32 Model & 26" x 37" for the Bellevue 27) but not the large size Full Front Façade.

	Madison Park™ 27 & Madison Park™ CD 27	Madison Park™ 32 & Madison Park™ CD 32	Madison Park™ 34 & Madison Park™ CD 34	Ravenna™ 33/40	Bellevue 27	Bellevue 32
Front Width	27"	32"	34"	31-1/2"	27"	32"
Height	18"	19-1/2"	24"	19-1/2"	18"	19-1/2"
Rear Width	17"	22"	24"	18"	17"	22"
Depth	15"	16"	16"	16"	15"	16"

CLEARANCES

SIDE-BY-SIDE COMPARISONS

	MADISON PARK	MADISON PARK CD	RAVENNA	BELLEVUE	
Models	Large, Medium, Small	Large, Medium, Small	Medium	Medium, Small	
Design Style	Traditional	Contemporary	Traditional	Traditional	
Interior Media	Ceramic Fiber Log Set	Glass Pebbles	Ceramic Fiber Log Set	Ceramic Fiber Log Set	
Glass Front	Ceramic	Ceramic	Ceramic	Ceramic	
Protective Barrier	Included	Included	Included	Included	
Interior Illumination	Included Large & Medium	Included Large & Medium	N/A	N/A	
Ceramic Fiber & Black Reflective Interior Liners	Required (choose 1)	Required (choose 1)	Required (choose 1)	N/A	
Surround Panels	Required (choose 1)	Required (choose 1)	Required (choose 1)	N/A	
Front Façade	Required (choose 1)	Required (choose 1)	Required (choose 1)	Required (choose 1)	
Decorative Trim	Optional	Optional	Optional	Optional	
Standard Blower	150 CFM Variable Speed	150 CFM Variable Speed	150 CFM Variable Speed	150 CFM Variable Speed	
Controls	Electronic	Electronic	Electronic	Electronic	
Multi-Function Touch Remote Control	Included	Included	Included	N/A	
Wireless Wall Mounted Control	N/A	N/A	N/A	Optional	
Hand Held Remote Control	N/A	N/A	N/A	Optional	
United States ANSI Listing	Z21.88 Heater Rated	Z21.88 Heater Rated	Z21.88 Heater Rated	Z21.88 Heater Rated	
United States AFUE Rated	Yes	Yes	No	Yes	
Canada CSA Listing	2.33 Heater Rated	2.33 Heater Rated	2.33 Heater Rated	2.33 Heater Rated	
Canada EnerGuide Rated	Yes	Yes	Yes	Yes	
Venting Configurations	3" Co-Linear	3" Co-Linear	3" Co-Linear	3" Co-Linear	
Warranty	20 Year Limited	20 Year Limited	20 Year Limited	20 Year Limited	





